

TEC**Industrial**

Hose Assemblies, Hydraulic Hoses, Fittings and Adapters

www.tecindustrial.ie | +353 1 457 3533

Email us at: sales@tecindustrial.ie

Unit C3 Weatherwell Business Park, Ninth Lock Road, Clondalkin, Dublin, D22 P803, Ireland

// 680AA



Fuel-oil delivery 10 bar (150 psi)

Tube: black synthetic elastomer.

Reinforcement: high tensile textile cords - antistatic wire ID \geq 13 mm.

Cover: black synthetic elastomer - abrasion, ozone and hydrocarbon resistant.

Application: general purpose fuel and oil delivery.

Constant operation: -10 °C +60 °C (+14 °F +140 °F)

⊕		⊖		⊙		⊙		⌒		⌘	⌚	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	13,00	0,51	10	150	30	450	48,0	1,89		0,140	0,10
8,0	5/16"	15,00	0,59	10	150	30	450	64,0	2,52		0,170	0,12
10,0	3/8"	17,00	0,67	10	150	30	450	80,0	3,15		0,200	0,14
13,0	1/2"	20,00	0,79	10	150	30	450	104,0	4,09		0,245	0,17
19,0	3/4"	27,00	1,06	10	150	30	450	152,0	5,98		0,395	0,27
25,0	1"	35,00	1,38	10	150	30	450	200,0	7,87		0,625	0,43