

47200**General purpose food quality S&D - PVC
FDA - EU 10/2011 A+B+C - AS 2070****Construction:** Transparent PVC - abrasion and ozone resistant**Reinforcement:** Steel helix wire**Use:** General purpose liquid food and alcoholic beverages suction and delivery - max 20% - Sterilize with 5% soda solution**Safety factor:** 3:1**Temperature:** -5 °C +60 °C (+23 °F +140 °F)

Item Code												
	mm	inch	mm	inch	bar	psi	mm	inch				%
2011483	10	3/8	16	0,63	15	225	40	1,50	90	0,170	0,115	60
2011485	13	1/2	19	0,75	7	100	52	2,00	85	0,205	0,138	60
2011487	14	9/16	20	0,79	6	90	56	2,25	85	0,220	0,150	60
2011489	16	5/8	22	0,87	6	90	64	2,50	85	0,250	0,170	60
2011492	18	23/32	26	1,02	6	90	72	2,75	85	0,320	0,215	60
2005446	20	13/16	28	1,10	5	75	80	3,00	85	0,340	0,230	60
2011495	22	7/8	30	1,18	5	75	88	3,50	85	0,380	0,255	60
2005448	25	1	33	1,30	5	75	100	4,00	85	0,530	0,360	60
2011497	30	1 3/16	38	1,50	4	60	120	4,75	85	0,620	0,420	60
2005450	32	1 1/4	40	1,57	4	60	128	5,00	85	0,655	0,440	60
2011499	35	1 3/8	45	1,77	4	60	140	5,50	85	0,800	0,540	60
2005452	38	1 1/2	48	1,89	4	60	152	6,00	85	0,855	0,570	30
2005454	40	1 9/16	50	1,97	3	45	160	6,25	85	0,895	0,605	30
2011501	45	1 3/4	55	2,17	3	45	180	7,00	80	1,100	0,740	30
2005456	51	2	61	2,40	3	45	204	8,00	80	1,230	0,830	30
2011503	60	2 3/8	72	2,83	2	30	240	9,50	80	1,700	1,140	30
2005458	63	2 1/2	75	2,95	2	30	252	10,00	80	1,775	1,190	30
2005460	70	2 3/4	84	3,31	2	30	280	11,00	80	2,030	1,365	30
2005462	76	3	90	3,54	2	30	304	12,00	70	2,450	1,650	30
2011505	80	3 1/8	94	3,70	2	30	320	12,50	70	2,565	1,720	30
2011508	90	3 1/2	104	4,09	2	30	360	14,00	70	3,000	2,020	30
2005464	102	4	116	4,57	2	30	408	16,00	70	3,480	2,340	30
2011513	152	6	172	6,77	2	30	608	24,00	70	7,300	4,910	20