

TEC**Industrial**

Hose Assemblies, Hydraulic Hoses, Fittings and Adapters

www.tecindustrial.ie | +353 1 457 3533

Email us at: sales@tecindustrial.ie

Unit C3 Weatherwell Business Park, Ninth Lock Road, Clondalkin, Dublin, D22 P803, Ireland

// 350LE



Steam 6 bar (90 psi) - Hot water 15 bar (225 psi)
FDA - arrêté du 09/11/94 D

Tube: white food grade EPDM.

Reinforcement: high tensile textile cords.

Cover: blue EPDM - heat, abrasion and ozone resistant.

Application: saturated steam and hot water delivery in general industrial applications. Specially designed for wash down use in the food and dairy industry.

Also suitable for liquid food and alcoholic beverages.

Constant operation: water -40 °C +120 °C (-40 °F +248 °F)
steam +165 °C (+330 °F)

⊙		⊕		⊖		⊗		⌒		⌘	⌚	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	6	90	60	900				0,360	0,25
16,0	5/8"	26,00	1,02	6	90	60	900				0,420	0,29
19,0	3/4"	31,00	1,22	6	90	60	900				0,590	0,40
25,0	1"	37,00	1,46	6	90	60	900				0,740	0,50
32,0	1 1/4"	46,00	1,81	6	90	60	900				0,930	0,63
38,0	1 1/2"	52,00	2,05	6	90	60	900				1,090	0,74
51,0	2"	67,00	2,64	6	90	60	900				1,660	1,12