







TEC**Industrial****Hose Assemblies, Hydraulic Hoses, Fittings and Adapters****www.tecindustrial.ie | +353 1 457 3533****Email us at: sales@tecindustrial.ie**

Unit C3 Weatherwell Business Park, Ninth Lock Road, Clondalkin, Dublin, D22 P803, Ireland

|  | |  | |  | |  | |  | |  | |
|---|--------|---|-------|---|-----|---|-------|---|--------|---|--|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft | |
| 25 | 1 | 35 | 1,38 | 10 | 150 | 100 | 4,00 | 100 | 0,690 | 0,465 | |
| 30 | 1 3/16 | 40 | 1,57 | 10 | 150 | 120 | 4,75 | 100 | 0,780 | 0,525 | |
| 32 | 1 1/4 | 42 | 1,65 | 10 | 150 | 128 | 5,00 | 100 | 0,820 | 0,555 | |
| 38 | 1 1/2 | 48 | 1,89 | 10 | 150 | 152 | 6,00 | 100 | 0,950 | 0,640 | |
| 40 | 1 9/16 | 50 | 1,97 | 10 | 150 | 160 | 6,25 | 100 | 1,000 | 0,675 | |
| 45 | 1 3/4 | 55 | 2,17 | 10 | 150 | 180 | 7,00 | 100 | 1,110 | 0,750 | |
| 51 | 2 | 61 | 2,40 | 10 | 150 | 204 | 8,00 | 100 | 1,240 | 0,835 | |
| 60 | 2 3/8 | 72 | 2,83 | 10 | 150 | 240 | 9,50 | 100 | 1,710 | 1,150 | |
| 63 | 2 1/2 | 75 | 2,95 | 10 | 150 | 252 | 10,00 | 90 | 1,780 | 1,200 | |
| 70 | 2 3/4 | 82 | 3,23 | 10 | 150 | 280 | 11,00 | 90 | 1,990 | 1,340 | |
| 76 | 3 | 88 | 3,46 | 10 | 150 | 304 | 12,00 | 90 | 2,140 | 1,440 | |
| 80 | 3 1/8 | 92 | 3,62 | 10 | 150 | 320 | 12,50 | 90 | 2,300 | 1,550 | |
| 90 | 3 1/2 | 102 | 4,02 | 10 | 150 | 360 | 14,00 | 90 | 2,700 | 1,815 | |
| 102 | 4 | 114 | 4,49 | 10 | 150 | 408 | 16,00 | 90 | 3,010 | 2,025 | |
| 110 | 4 5/16 | 122 | 4,80 | 10 | 150 | 440 | 7,25 | 80 | 3,210 | 2,160 | |
| 115 | 4 1/2 | 127 | 5,00 | 10 | 150 | 460 | 18,00 | 80 | 3,340 | 2,245 | |
| 120 | 4 3/4 | 134 | 5,28 | 10 | 150 | 600 | 24,00 | 80 | 4,500 | 3,025 | |
| 127 | 5 | 141 | 5,55 | 10 | 150 | 635 | 25,00 | 80 | 4,730 | 3,180 | |
| 152 | 6 | 166 | 6,54 | 10 | 150 | 760 | 30,00 | 80 | 5,960 | 4,010 | |
| 203 | 8 | 221 | 8,70 | 10 | 150 | 1015 | 40,00 | 70 | 9,810 | 6,595 | |
| 254 | 10 | 272 | 10,71 | 10 | 150 | 1270 | 50,00 | 60 | 13,430 | 9,030 | |

NA

LA

NEU

EMEA


SA


AP


AU

**202AA****General purpose S&D 10 bar (150 psi) - EPDM****Tube:** Black conductive EPDM**Reinforcement:** High tensile textile cords with embedded steel helix wire**Cover:** Black conductive EPDM - abrasion and ozone resistant**Use:** Water suction and delivery. Also suitable for mild chemicals and fertilizers in general industrial and agricultural applications**Safety factor:** ≤ 127 mm 3:1 ≥ 152 mm 2,5:1**Temperature:** -40 °C +100 °C (-40 °F +212 °F)
depending on conveyed chemical**// SYMBOLS**
 // INTERNAL DIAMETER

 // OUTSIDE DIAMETER

 // MAXIMUM WORKING PRESSURE

 // MINIMUM BURST PRESSURE

 // MINIMUM BEND RADIUS

 // WALL THICKNESS

 // WEIGHT